# Tuesday, 23 May 2023

International Journal on Advanced Science Engineering Information Technology

HOME ARCHIVES

# International Journal on Advanced Science, Engineering and Information Technology



International Journal on Advanced Science, Engineering and Information Technology (IJASEIT) is an international peer-reviewed Journal dedicated to interchange for the results of high quality research in all aspect of science, engineering and information technology. The journal publishes state-of-art papers in fundamental theory, experiments and simulation, as well as applications, with a systematic proposed method, sufficient review on previous works, expanded discussion and concise conclusion. As our commitment to the advancement of science and technology, the IJASEIT follows the open access policy that allows the published articles freely available online without any subscription.

## Scope

The journal scopes include (but not limited to) the followings

Science: Bioscience & Biotechnology, Agriculture, Chemistry & Food Technology, Environmental, Health Science, Mathematics & Statistics, Applied Physics.

Engineering: Architecture, Chemical & Process, Civil & structural, Electrical, Electronic & Systems, Geological & Mining Engineering, Mechanical & Materials.

Information Science, Artificial Intelligence, Computer Science, E-Learning & Education Learning, Multimedia, Knowledge Technology, Information System, Internet & Mobile Computing, Machine Learning.

Frequency: 6 issues per year

DOI: 10.18517/ijaseit

ISSN: 2088-5334



Template of Journal IJASEIT

Support Contact WAG :+62-82171-822448 E-mail :ijaseit@insightsociety.org

## The Map Authors



Keywords Cloud

## Tuesday, 23 May 2023

International Journal on Advanced Science Engineering Information Technology

HOME ARCHIVES

# **Editorial Team**

## Editor in Chief :

Rahmat Hidayat, (Scopus ID: 57191265401) Politeknik Negeri Padang, INDONESIA

#### Associate Editors :

Taufik, (Scopus ID: 23670809800), California Polytechnic State University, USA Haitham Alali, (Scopus ID: 43963007000), Amman Arab University, JORDAN Wan Mohtar Wan Yusoff, (Scopus ID: 15019967700), Univ. Kebangasan Malaysia, MALAYSIA Hailmah Badicze Zaman, (Scopus ID: 25825801600), Univ. Kebangasan Malaysia, MALAYSIA Son Radu, (Scopus ID: 7005251005), Universiti Putra Malaysia, MALAYSIA Mohd Razi Ismail, (Scopus ID: 55275091400), Universiti Putra Malaysia, MALAYSIA Kohei Nakano, (Scopus ID: 55275091400), Universiti Putra Malaysia, MALAYSIA Kohei Nakano, (Scopus ID: 740211766), Gifu University, JAPAN Kohei Nakano, (Scopus ID: 55946558300), Bogor Agriculture University, INDONESIA Sate Sampatagui, (Scopus ID: 55946558300), Bogor Agriculture University, INDONESIA Sate Sampatagui, (Scopus ID: 7801640661), Chiangmai University, THALAND Peeyush Soni, (Scopus ID: 7801640661), Chiangmai University, THALAND Yolanda Lechon Perez, (Scopus ID: 559577582400), Garconi University, ITALY Alessandra Pieroni (Scopus ID: 559577582400), Universiti Patra Malaysia, MALAYSIA Anton S Prabuwon, (Scopus ID: 55957782400), University of Rome Tor Vergata, ITALY Rita Muhamad Awang, (Scopus ID: 7006461145), University of Ruhuna, SRI LANKA Bich Huy Nguyen, (Scopus ID: 21632783000), King Adulaizz Univ, SAUDI ARABIA P Mangala C S De Silva, (Scopus ID: 20997582400), University of Neuhana, SRI LANKA Bich Huy Nguyen, (Scopus ID: 21633708300), King Adulaizz Univ, SAUDI ARABIA P Mangala C S De Silva, (Scopus ID: 2097563000), Linnersity of New England, AUSTRALIA Amitava Basu, (Scopus ID: 21833738300), Bidhan Chandra Krishi Vidyalaya, INDIA Shahrul Azman (Mohd Nach, (Scopus ID: 5367673200), University of Rome Tor Vergata, ITALY Ruben Paul Borg (Scopus ID: 534997900), University of Rome Tor Vergata, ITALY Ruben Paul Borg (Scopus ID: 534997900), University of Rome Tor Vergata, ITALY Ruben Paul Borg (Scopus ID: 5346483600), L-University of Rome Tor Vergata, ITALY Ruben Paul Borg (Scopus ID: 5346498300), University of Rome Tor Vergata, ITALY Ruben Paul Bo

#### Editors :

Novizar Nazir, (Scopus ID: 35503777500), Universitas Andalas, INDONESIA Rahadian Zainul, (Scopus ID: 56737195700), Universitas Negeri Padang, INDONESIA Ario Betha Juansilfero, (Scopus ID: 57189369470), Kobe University, JAPAN Zairi Ismael Rizman, (Scopus ID: 36959761800), Universiti Teknologi MARA (UITM) (Terengganu) MALAYSIA Shahreen Kasim, (Scopus ID: 36155431900), Universiti Tun Hussein Onn - MALAYSIA Chi-Hua Chen, (Scopus ID: 35799698800), National Chiao Tung University, TAIWAN



## The Map Authors



## ISSN: 2088-5334

# Tuesday, 23 May 2023

International Journal on Advanced Science Engineering Information Technology

HOME ARCHIVES

## Vol. 10 (2020) No. 1

## Articles

Methods for Software Visualization of Large Graph Data Structures

Velin Kralev, Radoslava Kraleva pages: 1-8 Full text DOI:10.18517/ijaseit.10.1.10739

#### Enhancing Prediction Method of Ionosphere for Space Weather Monitoring Using Machine Learning Approaches: A Review

Nor'asnilawati Salleh, Siti Sophiayati Yuhaniz, Sharizal Fadlie Sabri, Nurulhuda Firdaus Mohd Azmi pages: 9-15 Full text DOI:10.18517/ijaseit.10.1.10163

TEGDroid: Test Case Generation Approach for Android Apps Considering Context and GUI Events

Asmau Usman, Noraini Ibrahim, Ibrahim A Salihu pages: 16-23 Full text DOI:10.18517/ijaseit.10.1.10194

#### Quality Model for Massive Open Online Course (MOOC) Web Content

Wan Nurhayati Wan Ab Rahman, Hazura Zulzalii, Iskandar Ishak, Ahmad Wiraputra Selamat pages: 24-33 Full text DOI:10.18517/ijaseit.10.1.10192

## Case Study on Non-Functional Requirement Change Impact Traceability for Agile Software Development

 Adila Firdaus Arbain, Dayang Norhayati Abang Jawawi, Wan Mohd Nasir bin Wan Kadir, Imran Ghani

 pages: 34-40
 Full text

 DOI:10.18517/ijaseit.10.1.10176

#### A Study on Reuse-based Requirements Engineering by Utilizing Knowledge Pattern

Sabrina Ahmad, Zariza Hashim, Siti Azirah Asmai pages: 41-46 Full text DOI:10.18517/ijaseit.10.1.10168

#### The Development of Web-Based Emotion Detection System Using Keyboard Actions (EDS-KA)

Zuriana Abu Bakar, Ong Sze Seong pages: 47-57 Full text DOI:10.18517/ijaseit.10.1.10170

## An Analysis of Pre-service Teachers' Learning Process in Programming Learning

Seong-Won Kim, Youngjun Lee pages: 58-69 Full text DOI:10.18517/ijaseit.10.1.5723

## Bearing Fault Diagnosis Using Motor Current Signature Analysis and the Artificial Neural Network

Thoalfaqqar Ali Dhomad, Alaa Abdulhady Jaber pages: 70-79 Full text DOI:10.18517/ijaseit.10.1.10629

# Exploring the Use of Biometric Smart Cards for Voters' Accreditation: A Case Study of Nigeria Electoral Process

Akande Noah Oluwatobi, Toba Paul Ayeni, Tayo Oladiran Arulogun, Adebiyi Ayodele Ariyo, Kayode Anthonia Aderonke

pages: 80-89 Full text DOI:10.18517/ijaseit.10.1.8459

## Estimating Damaged Volume of Historic Pagodas in Bagan after Earthquake using 3D Hough Transform

 Thida Aung, Myint Myint Sein

 pages: 90-97

 Full text

 DOI:10.18517/ijaseit.10.1.8865

How Usability Defects Defer from Non-Usability Defects? : A Case Study on Open Source Projects

Nor Shahida Mohamad Yusop, John Grundy, Jean-Guy Schneider, Rajesh Vasa pages: 98-105 Full text DOI:10.18517/ijaseit.10.1.10225

Risk Evaluation Using Nominal Group Technique for Cloud Computing Risk Assessment in Healthcare

Nurbaini Zainuddin, Rasimah Che Mohd Yusuff, Ganthan Narayana Samy pages: 106-111 Full text DOI:10.18517/iijaseit.10.1.10169

# Statistical Comparison of Architecture Driven Modernization with other Cloud Migration Frameworks and Formation of Clusters

Mubeen Aslam, Lukman AB Rahim, Manzoor Hashmani, Junzo Watada pages: 112-119 Full text DOI:10.18517/ijaseit.10.1.10167

Automated Test Cases and Test Data Generation for Dynamic Structural Testing in Automatic Programming Assessment Using MC/DC

Rohaida Romli, Shahadath Sarker, Mazni Omar, Musyrifah Mahmod pages: 120-127 Full text DOI:10.18517/ijaseit.10.1.10166

A Tesseract-based Optical Character Recognition for a Text-to-Braille Code Conversion

Robert G. de Luna pages: 128-136 Full text DOI:10.18517/ijaseit.10.1.9956

Thin Films of Silver Nanowires for Flexible, Transparent, and Conductive (FTC) Electrodes

- Junaidi, Kemal Maulidiasani, Kuwat Triyana, - Khairurrijal pages: 137-144 Full text DOI:10.18517/ijaseit.10.1.5889

A Comparative Study of Segmentation Algorithms in the Classification of Human Skin Burn Depth





Template of Journal IJASEIT

Support Contact WAG :+62-82171-822448 E-mail :ijaseit@insightsociety.org

## The Map Authors



Keywords Cloud

P.N. Kuan, S. Chua, E.B. Safawi, H.H. Wang pages: 145-150 Full text DOI:10.18517/ijaseit.10.1.10227

Univariate Financial Time Series Prediction using Clonal Selection Algorithm Ammar Azlan, Yuhanis Yusof, Mohamad Farhan Mohamad Mohsin

pages: 151-156 Full text DOI:10.18517/ijaseit.10.1.10235

Development and Validation of Enterprise Architecture (EA) Readiness Assessment Model

Surya Sumarni Hussein, Mohd Naz'ri Mahrin, Nurazean Maarop, Nur Azaliah Abu Bakar pages: 157-163 Full text DOI:10.18517/ijaseit.10.1.9007

#### Multiple Sensor on Clustering Wireless Sensor Network to Tackle Illegal Cutting

Giva Andriana Mutiara, Nanna Suryana, Othman Mohd pages: 164-170 Full text DOI:10.18517/ijaseit.10.1.8849

## Improving the Accuracy of Ship Resistance Prediction Using Computational Fluid Dynamics Tool

Van Chinh Huynh, Gia Thai Tran pages: 171-177 Full text DOI:10.18517/ijaseit.10.1.10588

## A Comparative Study of Interactive Segmentation with Different Number of Strokes on Complex Images

Kok Luong Goh, Giap Weng Ng, Muzaffar Hamzah, Soo See Chai pages: 178-184 Full text DOI:10.18517/ijaseit.10.1.10240

#### Mathematical Models Selection on the Total Suspended Solid Mapping using Reflective Satellite Image Data

Hendrata Wibisana, Bangun Muljo S, Umboro Lasminto pages: 185-190 Full text DOI:10.18517/ijaseit.10.1.6750

#### Application of Time Series InSAR (SBAS) Method using Sentinel-1A Data for Land Subsidence Detection in Surabaya City

Ira Mutiara Anjasmara, Sendy Ayu Yulyta, Muhammad Taufik pages: 191-197 Full text DOI:10.18517/ijaseit.10.1.6749

#### The Implementation Guidelines of Digital Document Management System for Malaysia Public Sector: Expert Review

Azlina Ab Aziz, Zawiyah Mohammad Yusof, Umi Asma Mokhtar, Dian Indrayani Jambari pages: 198-204 Full text DOI:10.18517/ijaseit.10.1.10443

#### Digital Competences Relationship between Gender and Generation of University Professors

Andrea Basantes-Andrade, Marcos Cabezas-González, Sonia Casillas-Martín pages: 205-211 Full text DOI:10.18517/ijaseit.10.1.10806

#### Remote Sensing Data Integration of Landsat 8 and SRTM for Geomorphological Characteristics Identification in Karst Pringkuku, Pacitan, East Java

Silmi Afina Aliyan, Ayi Syaeful Bahri, Amien Widodo, Widya Utama pages: 212-218 Full text DOI:10.18517/ijaseit.10.1.6751

#### Vulnerability Assessment of Landslide Areas in Ci Manuk Upstream Watershed, Garut District, West Java Province

Muhammad Edgar Fauzan, Astrid Damayanti, Ratna Saraswati pages: 219-226 Full text DOI:10.18517/ijaseit.10.1.6755

#### Urgent Measure of Geospatial Parameters for Flood Modeling in Indonesia

Heri Andreas, Dina A Sarsito, Angga Trysa Yuherdha, Dhota Pradipta pages: 227-233 Full text DOI:10.18517/ijaseit.10.1.6743

#### Indonesian Text Classification using Back Propagation and Sastrawi Stemming Analysis with Information Gain for Selection Feature

Mahendra Dwifebri Purbolaksono, Feddy Dea Reskyadita, - Adiwijaya, Arie Ardiyanti Suryani, Arief Fatchul Huda pages: 234-238 Full text DOI:10.18517/ijaseit.10.1.8858

#### Developing and Validating an Instrument for Social Content Management

Wan Azlin Zurita Wan Ahmad, Muriati Mukhtar, Yazrina Yahya pages: 239-245 Full text DOI:10.18517/ijaseit.10.1.10269

#### The Acceptance of Braille Self-Learning Device

Zaid Haron Musa Jawasreh, Noraidah Sahari Ashaari, Dahlila Putri Dahnil pages: 246-252 Full text DOI:10.18517/ijaseit.10.1.10263

## Technology Integration to Promote Desire to Learn Programming in Higher Education

Nurul Faeizah Husin, Hairulliza Mohamad Judi, Siti Aishah Hanawi, Hazilah Mohd Amin pages: 253-259 Full text DOI:10.18517/ijaseit.10.1.10264

Modeling Methane Emission of Wastewater Anaerobic Pond at Palm Oil Mill Using Radial Basis Function Neural Network

Ledis Heru Saryono Putro, Dedik Budianta, Dedi Rohendi, Amin Rejo pages: 260-268 Full text DOI:10.18517/ijaseit.10.1.9577

#### Seismic Vulnerability Mapping to Support Spatial Plans in Lhokseumawe City Area

Deassy Siska, Herman Fithra, Nova Purnama Lisa, Nandi Haerudin, Muhammad Farid pages: 269-273 Full text DOI:10.18517/ijaseit.10.1.10276

#### The Role of Natural Gas in Indonesia CO2 Mitigation Action: The Environmental Kuznets Curve Framework

Dede Udayana Laksmana, Uka Wikarya pages: 274-285 Full text DOI:10.18517/ijaseit.10.1.10660

#### Assessing Eutrophication in the Coastal Bay by ASSETS Index Model

Huong Giang Le Thi, Nguyen The Nguyen Thi, Nurhamidah Nurhamidah, Tuan Anh Tran

fuzzy protein detection security rice data cours power comregression sources of the security rice data course power comregression sources of the security rice assays build assay the security of the security assays and the security of the regression of the security of the security of the security of the security of the regression of the security of the regression of the security of the regression of the security of the regression of the security of the regression of the security of



Member of

Ŷ



pages: 286-292 Full text DOI:10.18517/ijaseit.10.1.10621

pages: 293-297 Full text DOI:10.18517/ijaseit.10.1.6747

#### Underwater Photogrammetry Application for Coral Reef Mapping and Monitoring

Agung Budi Cahyono, Andreas Catur Wibisono, Dian Saptarini, Rizki Indra Permadi, Yanto Budisusanto, Husnul Hidayat

# The Rainfall Effect Analysis of Landslide Occurrence on Mount Slopes of Wilis

Lalu Muhamad Jaelani, Rizha Fahlefi, Mohammad Khoiri, Juan Pandu Gya Nur Rochman pages: 298-303 Full text DOI:10.18517/ijaseit.10.1.6876

#### Numerical Study: Effect of Various Link Length to Lateral Force in Eccentrically Braced Frame

- Nidiasari, Sabril Haris, Lulu Ulwani Umry pages: 304-310 Full text DOI:10.18517/ijaseit.10.1.10308

#### Experimental Study of Indonesian Low-Cost Glass Fiber Reinforced Elastomeric Isolators (GFREI)

- Tavio, Usman Wijaya pages: 311-317 Full text DOI:10.18517/ijaseit.10.1.8054

## Earthquake Safe Houses Training for Tsunami Preparedness in West Sumatra

Febrin Anas Ismail, Abdul Hakam, Taufika Ophiyandri pages: 318-324 Full text DOI:10.18517/ijaseit.10.1.7850

#### Real Time Bridge Dynamic Response: Bridge Condition Assessment and Early Warning System

Muhammad Riyansyah, Pratama Budi Wijayanto, Bambang Riyanto Trilaksono, Seno Adi Putra, Dina Shona

pages: 325-330 Full text DOI:10.18517/ijaseit.10.1.9463

I aila

# Livelihoods of Mountainous Sites in Vietnam and Philippines: Are They Threatened from Cold Spell and Typhoon?

Hanilyn Hidalgo, Nguyen Hoang Nam, Nguyen Thi Bich Phuong pages: 331-343 Full text DOI:10.18517/ijaseit.10.1.10701

## Growth Performance and AMMI Yield Stability Analysis of Five New Maize Hybrid Populations

- Rustikawati, Atra Romeida, Eko Suprijono, Catur Herison pages: 344-350 Full text DOI:10.18517/ijaseit.10.1.3862

# Synthesis and Characterization of Pectin–Chitosan crosslinked of BADGE for Adsorbents Candidate of Textile Dve Waste Water

Budi Hastuti, Saptono Hadi, Warih Purwendah pages: 351-355 Full text DOI:10.18517/ijaseit.10.1.10655

#### Effects of Organic Materials and Rainfall Intensity on the Productivity of Oil Palm Grown under Sandy Soil Condition

Sri Gunawan, Maria Theresia Sri Budiastuti, Joko Sutrisno, Herry Wirianata pages: 356-361 Full text DOI:10.18517/ijaseit.10.1.11001

#### The Characterization of Ficus lyrata Warb Fruit Extract and the Effect on Toxicity, Physicochemical, and Microbiology Properties of Chicken Carcass

Dwi Wahyudha Wira, Efri Mardawati, Mohamad Djali, Roostira Lobo Balia pages: 362-367 Full text DOI:10.18517/ijaseit.10.1.9770

#### Isotopic Tracing of Phosphorus Uptake in Oil Palm Seedlings Leaf Axil Using 32P Labelled

Warmanti Mildaryani, Mujiyo Mujiyo, Widyatmani Sih Dewi, Djoko Poernomo pages: 368-373 Full text DOI:10.18517/ijaseit.10.1.11119

#### Synthesis of Epoxide and Polyol Compounds as Intermediates for Biolubricant from Soybean Oil

Muhammad Said, Bobbie Rizkie Mandhala Hermanto, Muhammad Aidil Defitra, Febri Sandi, Risky Vernando pages: 374-380 Full text DOI:10.18517/ijaseit.10.1.10463

#### Secondary Macronutrients Up-Take, Root Development, and Chlorophyll Content of Local Rice Varieties Grown under System of Rice Intensification (SRI) vs. Conventional Methods

Bambang Heri Isnawan, - Supriyono, - Supriyadi, - Samanhudi pages: 381-388 Full text DOI:10.18517/ijaseit.10.1.11057

#### Effects of Ripening Level and Processing Delay on the Characteristics of Oil Palm Fruit Bunches

Adi Ruswanto, Ari Handono Ramelan, Danar Praseptiangga, Ida Bagus Banyuro Partha pages: 389-394 Full text DOI:10.18517/ijaseit.10.1.10987

#### Influence of Acoustic Waves on the Shelf Life Quality of Broccoli (Bsassica oleracea var. italic)

Dixie Pablo Asuncion, Jeffrey A. Lavarias, Andres M Tuates Jr, Carolyn Grace G. Somera, Ruel G. Peneyra pages: 395-399 Full text DOI:10.18517/ijaseit.10.1.8363

## Combination of Electrocogulation and Aeration Processes by Addition NaCI for Leachate Treatment

- Rusdianasari, Adi Syakdani, Yohandri Bow, Tresna Dewi, Achmad Ja'far Shodiq, Susila Arita pages: 400-406 Full text DOI:10.18517/ijaseit.10.1.11012

#### Fog Harvesting and IoT based Environment Monitoring System at the Ilalo volcano in Ecuador

David Carrera-Villacrés, Jose Luis Carrera Villacrés, Torsten Braun, Zhongliang Zhao, Javier Gómez, Joffre Quinteros-Carabalí pages: 407-412 Full text DOI:10.18517/ijaseit.10.1.10775

## SMILE: Smart Monitoring IoT Learning Ecosystem

Roberta Avanzato, Francesco Beritelli, Francesco Di Franco, Michele Russo pages: 413-419 Full text DOI:10.18517/ijaseit.10.1.11144

## Tuesday, 23 May 2023

International Journal on Advanced Science Engineering Information Technology

HOME ARCHIVES

International Journal on Advanced Science, Engineering and Information Technology, Vol. 10 (2020) No. 1, pages: 400-406, DOI:10.18517/ijaseit.10.1.11012

# Combination of Electrocogulation and Aeration Processes by Addition NaCl for Leachate Treatment

- Rusdianasari, Adi Syakdani, Yohandri Bow, Tresna Dewi, Achmad Ja'far Shodiq, Susila Arita

## Abstract

Leachate is water which is formed in a pile of garbage that dissolves a lot of existing compounds so that it has a very high pollutant content, especially organics substances. Leachate has the potential to cause water pollution, both surface water, ground water and underground water, so it needs to be managed properly. Leachate processing uses a combination of electrocoagulation and aeration methods. The objective of this study is to determine leachate characteristics before and after the processes, the optimum treatment conditions, and the effectiveness of the treatment processes in reducing pollutant content. Electrocoagulation is able to reduce the characteristics of the waste pollutant content in terms of increasing pH and decreasing total disolved solid (TDS), total suspended solid (TSS), chemical oxygen demand (COD), biological oxygen demand (BOD5), and waste turbidity. This condition occurs due to the process of coagulation is the dissolution of ande metal (M+), which reacts with hydroxyl ions (OH-) to form coagulants. The experiment was conducted in batch, where the leachate is put into an electrochemical call containing 2 aluminum electrodes with dimensions of 10 cm x 10 cm. The parameters varied are the aeration process and variations in the addition of XaCI. The optimum conditions are achieved in the electrocoagulation process with aeration and the addition of 2 g/L NaCI. The most significant processing effectiveness of the process is TDS 34.06%, TSS 814.6%, COD 54.26%, BOD5 53.76%, and turbidity 29.2% respectively.

#### Keywords:

leachate; aeration; electrocoagulation; grbage; treatment.

Viewed: 1155 times (since abstract online)

ite this paper 🛛 🔊 download

Show fulltext



Kevwords Cloud

# Combination of Electrocogulation and Aeration Processes by Addition NaCl for Leachate Treatment

Rusdianasari<sup>#</sup>, Adi Syakdani<sup>#</sup>, Yohandri Bow<sup>#</sup>, Tresna Dewi<sup>\*</sup>, Achmad Ja'far Shodiq<sup>+</sup>, Susila Arita<sup>^</sup>

<sup>#</sup>Chemical Engineering Department, Politeknik Negeri Sriwijaya, Jl Srijaya Negara,Palembang, 30139, Indonesia E-mail: rusdianasari@polsri.ac.id, adis@polsri.ac.id, yohandribow@polsri.ac.id

<sup>\*</sup>Electrical Engineering Department, Politeknik Negeri Sriwijaya, Jl Srijaya Negara,Palembang, 30139, Indonesia E-mail: tresna\_dewi@polsri.ac.id, a\_taqwa@yahoo.com

<sup>+</sup>Chemical Engineering Department, Universitas Indonesia, Jl Margonda Raya, Depok, 16424, Indonesia E-mail: jafarshodiq.shahab@gmail.com

<sup>^</sup>Chemical Engineering Department, Universitas Sriwijaya, Jl Raya Prabumulih Km 32 Inderalaya, Indonesia E-mail: susilaarita@ft.unsri.ac.id

*Abstract*— Leachate is water which is formed in a pile of garbage that dissolves a lot of existing compounds so that it has a very high pollutant content, especially organics substances. Leachate has the potential to cause water pollution, both surface water, ground water and underground water, so it needs to be managed properly. Leachate processing uses a combination of electrocoagulation and aeration methods. The objective of this study is to determine leachate characteristics before and after the processes, the optimum treatment conditions, and the effectiveness of the treatment processes in reducing pollutant content. Electrocoagulation is able to reduce the characteristics of the waste pollutant content in terms of increasing pH and decreasing total disolved solid (TDS), total suspended solid (TSS), chemical oxygen demand (COD), biological oxygen demand (BOD5), and waste turbidity. This condition occurs due to the process of coagulation of pollutants by applying electric current to electrochemical reactions. The working principle of electrocoagulation is the dissolution of anode metal (M+), which reacts with hydroxyl ions (OH-) to form coagulants. The experiment was conducted in batch, where the leachate is put into an electrochemical cell containing 2 aluminum electrodes with dimensions of 10 cm x 10 cm. The parameters varied are the aeration process and variations in the addition of NaCl. The optimum conditions are achieved in the electrocoagulation process with aeration and the addition of 2 g/L NaCl. The most significant processing effectiveness of the process is TDS 34.06%, TSS 81.46%, COD 54.26%, BOD5 53.76%, and turbidity 92.92% respectively.

Keywords—leachate; aeration; electrocoagulation; grbage; treatment.

# I. INTRODUCTION

Leachate is the liquid formed by decomposing a pile of garbage that dissolves into compounds with a very high pollutant content, especially organic substances. The liquid fills cavities in the garbage. If the capacity exceeds the wastewater pressure capacity, then the liquid comes out and extracts the organic and inorganic materials resulting from the physical, chemical, and biological processes that occur in the waste. Leachate has the potential to cause water pollution, both surface water, groundwater, and underground water; therefore, proper treatment is necessary to prevent the harmful effect of leachate [1]-[4]. Leachate contains organic compounds (hydrocarbons, humic acids, sulfates, tanates, and gallates) and inorganic (sodium, potassium, calcium, magnesium, chlorine, sulfate, phosphate, phenol, nitrogen and heavy metal compounds) which is highly polluting the soil environment. Concentrations of these components in leachate can reach 1000 to 5000 times higher than concentrations in groundwater [5]-[8].

Appropriate counter measures must be taken to avoid environmental pollution caused by the leachate. The methods to prevent leachate recirculate back into landfills are biological, chemical, and membrane treatments [9], [10]. Leachate treatment by circulating back into the landfill requires a large amount of energy and is less effective during the rainy season. Biological leachate treatment is considered less effective in reducing metal content in leachate, whereas chemical and membranes treatment are also considered to be less effective because they require many chemicals and are relatively expensive. The cheap and electromechanically effective method is the electrocoagulation process [11]-[15].

Electrocoagulation is a cheap and effective method of processing industrial waste [16], [17]. Electrocoagulation is an electrochemical method for water and wastewater treatment where an anode occurs in the release of active coagulant in the form of metal ions (usually Al or Fe) into solution. At the cathode, the electrolysis reaction occurs in the form of the release of hydrogen gas [18]-[20]. To increase the effectiveness of decreasing metal ions and other substances contained in the waste, the researchers made variations in the addition of sodium chloride (NaCl) and the aeration process in the processing of the leachate [21], [22].

Aeration technique is one of the wastewater treatment conducted by adding oxygen to liquid waste. Oxygen addition is to capture the pollutant in the waste; therefore, pollutant concentration is reduced or even eliminated. Substances captured can be gases, liquids, ions, colloids, or other mixed materials; therefore, the combination of electrocoagulation and aeration methods can be used to treat leachate properly [23]-[26].

Leachate waste management is intented to minimize the volume, concentration and toxicity of pollutant waste contained in the waste leachate. Liquid waste must be treated until it fulfilled the requirements for disposal. Some researchers hypothesize that this combination of electrocoagulation and aeration methods can be used to treat leachate wastewater properly [27].

The purpose of this study is to analyze leachate wastewater based on the characteristics of the leachate before and after treatment with parameters pH, TDS, TSS, COD, BOD5, and turbidity and determine the optimum process conditions (NaCl concentration and aeration process) on the quality of treated leachate.

## II. MATERIAL AND METHODE

Leachate sample in the pond of a landfill in Garbage Landfill, Sukawinatan, Palembang City, South Sumatra, Indonesia, were examined for the physical and chemical characteristic. The physical parameters tested were the pH, total suspended solid (TSS), total dissolved solid (TDS) and turbidity. Chemical test involves determination of biological oxygen demand (BOD) and chemical oxygen demand (COD). After the initial characteristics of the raw leachate were obtained, electrocoagulation was conducted to treat the raw leachate samples in order to remove the pollutants.

Figure 1 shows the instrumentation using this study consists of electrolysis displaying a direct current power supply (DC), a cathode and anode, and the electrolyte solution (NaCl). During the process, the voltage used is 12V and the contact time is two hours with the addition of NaCl at intervals of 0.5 gr/L to 2 g/L. This analysis is used in leachate materials and the results of waste leachate treatment using a combination of electrocoagulation and aeration methods. In this research, aluminum electrodes were used as

the cathode and anode with dimension 10 cm long, 10 cm wide and 0.1 cm thick.



Fig. 1 Electrocoagulation and aeration experimental setup

This research was run in batch modes. Each pair of the similar plates were placed 3 cm. However, this research used small electric current by a direct power supply to the circuit (12V).

## **III. RESULTS AND DISCUSSION**

## A. Leachate Characterization

Preliminary analysis of raw leachate from the Sukawinatan landfill waste collection pond, Palembang City, South Sumatra, can be seen in Table 1.

 TABLE I

 INITIAL CHARACTERIZATION OF LEACHATE WASTE

No	Parameter	Unit	Results	Quality Standard*
1	pН	-	7.73	6.0-9.0
2	TDS (**)	mg/L	8963	2000
3	TSS	mg/L	151	100
4	COD	mg/L	129	300
5	BOD <sub>5</sub>	mg/L	42.6	150
6	Turbidity	NTU	40.1	-

<sup>\*</sup> Minister of the Environment Regulation No.68 Year 2016 and (\*\*) No. 5 of 2014

From the analysis of Sukawinatan landfill waste disposal characteristics in Table 1, it can be seen that there are several parameters in the waste that have met the quality standards where the waste may be discharged into the environment, including parameters pH, BOD5, and COD from the waste. While the parameters of TDS and TSS do not meet the quality standard. Therefore, it is still necessary to process this waste.

The leachate pH value taken from the Sukawinatan landfill waste has reached the quality standard that is allowed to be disposed of in the environment. The high pH value in this leachate is caused by the  $NH_3$  content in the waste, and the low  $CO_2$  content, the presence of hydroxide salts dissolved in the waste also affects increasing the pH value. The waste ph is in the range of pH 7.5-8 that shows the waste still contains acidification. This acidification is caused by the organic decay in the waste substances; therefore, pH value tends to be neutral. The proposed treatment process increases the pH value in the liquid by reducing acidification agents (such as  $CO_2$  and  $H_2S$ ) using

aeration process and also due to the formation of alkali hydroxide compounds from the electrocoagulation reaction.

TDS, TSS, and turbidity (turbidity) are parameters that significantly affect the quality of waste. In Table 1, TDS and TSS from leachate are higher than the established quality standards. The high TDS indicates that the waste contains a lot of dissolved solids, which is indicated by its ability to conduct electricity, while too high TSS indicates that the waste has many suspended solids and can directly cause turbidity in water. TSS and turbidity tend to be linear because TSS and turbidity both indicate the number of impurities that causes turbidity of wastewater. This parameter has a high impact on the waste ecosystem indirectly, namely the decrease in DO (Dissolved Oxygen) levels of the waste that affects the life of aquatic organisms and soil fertility and directly the impurity enter the respiratory system and organism's metabolism. This condition can endanger the survival of aquatic organisms.

BOD5 and COD characterize large contamination of pollutants in water. From Table 1, it can be seen that the BOD5 and COD values are below the quality standards set for waste disposal into the environment, which is higher compared to clear water. This treatment is also intended to reduce the content of BOD5 and COD to get more transparent water. COD value in wastewater shows the amount of material in wastewater, both organic and nonorganic, which can be oxidized (excluding ammonia oxidation). The BOD5 value in wastewater only shows the amount of material in wastewater that can be biodoxically oxidized (biodegradable materials), including ammonia oxidation. COD is always higher than the BOD value, and the COD/BOD ratio is usually determined to determine the ability of the waste to be biologically degraded.

## B. Characterization of leachate after processing

The result analysis of leachate, which has been processed using the electrocoagulation process with aluminum electrodes based on the influence of NaCl concentration and the presence or absence of aeration, can be seen in Table 2 and 3.

After leachate treatment, shown in Table 2 and Table 3, the number of pollutants contained in leachate decreases, indicated by an increase in pH and a decrease in the value of TDS, TSS, COD. BOD5 and turbidity. This contaminant content reduction occurs due to the electric coagulation process that binds the contaminant content to be the floating and the sediment to separate the waste solution. This process separates the pollutant inside the waste, and processed waste has better parameters than before.

 TABLE II

 LEACHATE ANALYSIS RESULTS USING ELECTROCOAGULATION PROCESS

 WITH A COMBINATION OF AERATION PROCESSES

NaCl	Parameters							
addition (g/L)	рН	TDS mg/L	TSS mg/L	COD mg/L	BOD5 mg/L	Turbi dity NTU		
0	8.02	8180	135	77	25.6	32.5		
0.5	8.09	8070	103	75	25	18.5		
1.0	8.12	7600	96	72	22.7	14.9		
1.5	8.14	6690	53	68	22.3	10.4		
2.0	8.21	5910	28	59	19.7	2.84		

TABLE III LEACHATE ANALYSIS RESULTS USING ELECTROCOAGULATION PROCESS WITHOUT COMBINATION OF AERATION PROCESSES

NaCl	Parameters						
addition (g/L)	рН	TDS mg/L	TSS mg/L	COD mg/L	BOD5 mg/L	Turbi dity NTU	
0	8.02	8180	135	77	25.6	32.5	
0.5	8.09	8070	103	75	25.0	18.5	
1.0	8.12	7600	96	72	22.7	14.9	
1.5	8.14	6690	53	68	22.3	10.4	
2.0	8.21	5910	28	59	19.7	2.84	

Aeration also provides the effect of decreasing contaminants in waste, which can be proven by comparing Table 2 and Table 3. Table 2 uses a new aeration process while Table 3, without the aeration process. Aeration helps to reduce the pollutant found in waste. Aeration can increase dissolved oxygen in water, reduce the gaseous elements present in waste ( $CO_2$ ,  $H_2S$ ), and at the same time, as an oxidizing agent that causes easily oxidized substances to get enough oxygen supply so that oxidation reactions can occur and oxidized substances separate from solution.

The best characteristics of leachate occur in the variation of the aeration process and the addition of 2 g/L, consists of pH 8.21, TDS 5910 mg/L, TSS 28 mg/L, COD 59 mg/L, BOD5 19.7 mg/L, turbidity 2.84 NTU. This indicates that the quality of leachate after being processed by the electrocoagulation method is below the environmental quality standard, as stated in the Regulation of the Minister of Environment No.68 Year 2016. TDS value is not below the quality standard value, due to the Minister of Environment Regulation Life No. 5 of 2014 states that the TDS quality standards are intended for class I water (raw water for drinking water).

# C. Effects of aeration process and NaCl addition to leachate after electrocoagulation preocessing

## 1) Effect of aeration processes and NaCl additional to pH

Hydrogen is a physical property that characterizes the acidity of a substance in the range of values from 0-14. The standard pH quality value for waste that may be discharged into the environment is between pH 6.0-9.0, which means that the initial leachate has been considered safe to be discharged into the environment. Leachate contains ammonia obtained from the decay of organic substances contained in the waste and causes it to become an alkaline solution.

After the electrocoagulation process is carried out, some alkali hydroxide content is formed as a result of the alkalization process of aluminum metal and other alkaline earth metals present in water. This process is oxidized to form metal ions in the anode and bind with hydroxide (OH) ions resulting from water reduction ( $H_2O$ ), which occurs at the cathode. The oxidation forms alkaline hydroxide compounds that are base and cause an increase in pH value.

Alkaline hydroxide is a base substance; therefore, the pH of the solution increase, as shown in Figure 2. The increasing salt concentration causes an improvement in the electrical conductivity of the solution. The more NaCl added results in an increase in electrical conductivity or a decrease

in the resistance of the type of solution. If the resistivity of the type of solution decreases, the resistance of the solution is also reduced. This condition indicates that the electric current flowing becomes more significant and more impact on the more alkali hydroxide formed. Therefore, higher levels of NaCl causes an increase in pH.

Figure 2 shows that the aeration process increases the pH value of waste due to carbon dioxide (CO<sub>2</sub>) content in leachate, which is an acidic substance. Air flowed through the solution draw CO<sub>2</sub> dissolved weakly in the water; therefore, CO<sub>2</sub> diffuses into the air beforehand. This event reduces the concentration of CO<sub>2</sub> in water and makes the solution loses the acidic carrier substance. Aeration can reduce the H<sub>2</sub>S compound, which is a strong acid by oxidizing it to produce water and free sulfur. The oxidation causes an increase in pH value when the electrocoagulation process is combined with the aeration process. From Figure 2, the optimum condition of the process is obtained in the electrocoagulation process with the highest combination of aeration and NaCl addition processes.



Fig. 2 Effect of aeration processes and NaCl concentration on pH

## 2) Effect of aeration processes and NaCl addition to TDS

TDS is the solid weight in the form of organic and nonorganic substances that are dissolved in the solvent and filtered in a 0.2  $\mu$  m sieve from the sample that has been clarified after heating the sample at a temperature of 105°C to have a fixed weight. The solid is not a suspended solid but is dissolved in solution.

The electrocoagulation process decreases waste TDS value due to the coagulation of some contents and separated from the waste. The decrement in TDS occurs when double layer compression occurs around the species due to interactions with ions formed from oxidation in the electrodes. The ion causes a decrease in repulsion between particles in water to make the coagulation process occurs.

The addition of NaCl causes better interaction between ions due the increment of electrical conductivity in the solution increases; therefore, more substances coagulated in solution.

Aeration has little ability to reduce the TDS value of the solution because aeration is less efficient in removing soluble substances. Figure 3 shows that aeration can reduce the TDS value because this process can oxidize iron and manganese in leachate and form insoluble compounds that can be separated. The alkaline solution also accelerates the manganese oxidation process that dissolved solids in water decrease.



Fig. 3 Effect of aeration processes and NaCl concentration on TDS

# 3) Effect of aeration processes and NaCl addition to TSS

Total Suspended Solids (TSS) are suspended materials (> 1-micrometer diameter) that are held in a millipore filter with a pore diameter of 0.45 micrometers. Suspended solids are solids with a larger diameter than dissolved and colloidal solids, and suspended solids tend to be visible and increases turbidity in water. From Figure 4, it can be seen that the TSS value gradually decreases after electrocoagulation and aeration. The process of reducing TSS in electrocoagulation occurs when solid material from a suspended solid undergoes an adsorption process into the coagulant (Al(OH)<sub>3</sub>). The results of this adsorption separate the suspended content from the waste to decrease TSS value. When NaCl is added to the sample, the TSS reduction is accelerated. The reduction is proportional to NaCl addition due to an increase in electrical conductivity result in the production of Al(OH)<sub>3</sub>, which occurs in the electrode increases. Al(OH)<sub>3</sub> is a coagulant compound that can quickly precipitate suspended solids, the more the amount of Al(OH)<sub>3</sub>, the better the coagulation process takes place.



Fig. 4 Effect of aeration processes and NaCl concentration on TSS

Aeration is also an influential factor in reducing TSS levels in this process. Aeration is a physical method that is carried out by injecting air into the waterbody. Air bubbles obtained from the aeration process directly function as a dispersing media of coagulant (Al(OH<sub>3</sub>) formed the suspended substances that are easier to contact and bond with the coagulant, in addition to that the aeration process also functions as a transport media in the form of a suspension substance in the form of float that contaminants can separate more easily. The optimum conditions are obtained with increasing salt concentration and the aeration process in water.

## 4) Effect of aeration processes and NaCl addition to COD

COD is the amount of oxygen needed to oxidize organic and inorganic compounds in the waste. High levels of COD indirectly indicates the number of contaminant compounds in water that can be chemically oxidized. COD indicates the overall chemicals in waste that can be oxidized, while BOD5 only indicates the number of substances that are easily oxidized by bioorganisms biologically in the waste.

Figure 5 shows that the addition of NaCl increases the solution conductivity and increase in alum  $(Al(OH)_3)$  production. This process decreases the waste content in the sample. Aeration prepares a relatively large supply of oxygen for the oxidation process of iron and manganese, and form a sediment at the bottom of the liquid surface. Data in Figure 5 shows that the aeration process and the amount of NaCl dissolved in the waste reduces the COD value. Processes that include aeration can reduce COD content by about 5% better than those without aeration.



Fig. 5 Effect of aeration processes and NaCl concentration on COD

## 5) Effect of aeration processes and NaCl addition to BOD5

BOD5 is the amount of oxygen needed by bacteria during the breakdown of organic compounds under aerobic conditions for 5 days. The measurement process is in 5 days to ensure the number of organic compounds described had reached 70%. The BOD5 value indicates the number of substances in waste that is easily degraded biologically. A high BOD5 value plays an essential role in supporting the growth of algae and aquatic organisms. Bacterial population affects the level of water pollution.

The electrocoagulation process produces an adsorber that binds most of the water contaminants in water, including organic substances. Organic substances are separated from the solution that the total oxygen used to oxidize organic content in waste is also reduced. In the previous parameters, NaCl increases the conductivity of the solution and the amount of coagulant formed while aeration can increase the homogeneity of the solution with the coagulant formed and provide additional oxygen to the body of water, which causes oxygen to oxidize some of the organic substances contained in the leachate and organic waste content in the sample decreases.



Fig. 6 Effect of aeration processes and NaCl concentration on BOD5

Figure 6 shows that the aeration process and the higher addition of NaCl added to the sample causes a decrease in BOD5. From Figure 6, it can be concluded that the increase of salt addition increases solution electrolysis, and the combination with the aeration process provides optimum conditions in the process of leachate treatment by electrocoagulation.

# 6) Effect of aeration processes and NaCl addition to turbidity

Turbidity is the amount of light that can be refracted by a sample when passed light. The refraction of light occurs due to the occurrence of substances that are able to refract the light. In contrast to TSS, turbidity values are not only affected by suspended solids but also affected by the number of colloids contained in the sample. It should be noted that color intensity is not a parameter in measuring turbidity.

The effect of adding NaCl and the aeration process also causes a decrease in turbidity values to take place better, as shown in Figure 6. NaCl added to the solution can cause a potential increase in the turbidity value of the solution, but the effect is not proportional to increasing  $Al(OH)_3$  coagulants. The slight addition of NaCl is not proportional to the reduced levels of pollutants in the waste due to coagulation by coagulants, that is what causes the NaCl effect in the electrocoagulation process to bring a positive correlation to impairment turbidity of waste. Aeration can expand the contact between the solution and the coagulant, which causes more flocculants to form and settle to the bottom of the water. The float formation is faster due to the aeration process.



Fig. 7 Effect of aeration processes and NaCl addition to turbidity

# D. The effectiveness of the electrocoagulation method in processing leachate

Effectiveness is a comparative value that shows the ratio between changes in the initial and after the experiment leachate. Processing for each electrocoagulation leachate treatment parameter is not the same since each parameter has its response in receiving the electrocoagulation treatment process. Changes in TDS values have the least effective among other parameter changes, while turbidity has the most significant processing effectiveness compared to other parameters

Figures 8 and 9 show that the addition of NaCl and the aeration process have a positive effect in increasing the value of the effectiveness of leachate treatment. Both of these variations have a considerable influence on increasing the value of the effectiveness of the process. From Figures 8 and 9, it can be concluded that the most effective electrocoagulation process is a combination of aeration processes and NaCl additions to the leachate sample.



Fig. 8 Electrocoagulation effectiveness of NaCl addition with combination of aeration processes



Fig. 9 Electrocoagulation effectiveness of NaCl addition without combination aeration processes

## IV. CONCLUSION

The most effective of the electrocoagulation process with the aeration process occurred in the addition of sodium chloride 2 g/L, which consists of the TDS value of 34.06%, TSS 81.46%, COD 54.26%, BOD5 53.76%, and turbidity While 92.92%. the highest effectivity of the electrocoagulation process without the aeration process occurs in the addition of 2 g/L sodium chloride, consists of the TDS value of 26.59%, TSS 54.3%, COD 49.61%, BOD5 49.06%, and turbidity 63.34 %. The result proves that the aeration variations process and the addition of sodium chloride increase the value of the effectiveness of the process. The optimum condition of the electrocoagulation process using aluminum electrodes is in a process that is combined with the aeration process and occurs at the highest addition of salt, which is 2 g/L. This indicates that the aeration process and the addition of NaCl reduce the level of pollutants in the waste.

## ACKNOWLEDGMENT

Authors would like to thank Politeknik Negeri Sriwijaya for supporting and facilitating this research.

## REFERENCES

- J. Ding, L. Wei, H. Hung, Q. Zhao, W. Hou, F. T. Kabuley, Y. Yuan, D.D. Dionysiou, Tertiary Treatment of Landfill Leachate by an Integrated Electro-Oxidation/Electro-Coagulation/Electro-Reduction process: Performance and mechanism, Journal of Hazardous Materials, Vol. 351, pp 90-97, 2018
- [2] S. H. Ammar, N.N. Ismail, Ali D. Ali, and W. M. Abas, "Electrocoagulation technique for refinery wastewater treatment in an internal loop split-plate airlift reactor", Journal of Environmental Chemical Engineering, vol. 7 (6), 2019.
- [3] Governor's Regulation, South Sumatera Governor Regulation No. 08 on Liquid Waste Quality Standards for Other Industries, 2012 (in Indonesian)
- [4] M. K. N. Mahmad, M. R. Rozainy, I. Abustan, and N. Baharun. Procedia Chem. 19, pp 681-686, 2016.
- [5] G. Hassani, A. Alinejad, A. Sadat, A. Esmaeili, M. Ziaei, A. A. Bazrafshan, and T. Sadat. Int. J. Electrochem. Sci. 11, pp 6705-6718, 2016.

- [6] Rusdianasari, A. Taqwa, Jaksen, and A. Syakdani, "Treatment optimization of electrocoagulation (EC) in purifying palm oil mill effluents (POMEs)". J. Eng. Technol. Sci. Vol. 49 (5) pp 604-617, 2017.
- [7] M. Poveda, Q. Yuan, J. Oleszkiewicz. Int. J. of Env. Csi. Dev. 7, 4, 2016.
- [8] A. Meidinariasty, Rusdianasari, Y. Bow, I. Rusnadi, and A.L. Fuadi. "Treatment of leachate from garbage using electrocoagulation type MP-P (monopolar-paralel) methode", J. Phys: Conf.Ser. 1167 012054, 2019.
- [9] Darmadi, M. R. Lubis, and Adisalamun, "The treatment of hospital wastewater using iron electrode electrocoagulation: Analysis by response surface methodology", Journal of Chemical Engineering and Environment, vol. 14 no. 2, page 112-119, 2019.
- [10] A. Ibrahim and A. Z. Yaser, "Colour removal from biologically treated landfill leachate with tannin-based coagulant", Journal of Environmental Chemical Engineering, vol. 7 (6), 2019.
- [11] M. Pirsaheb, E. Azizi, A. Almasi, M. Soltanian, T. Khosravi, M. Ghayebzadeh, and K. Sharafi, "Evaluating the efficiency of electrochemical process in removing COD and NH<sub>4</sub>-N from landfill leachate", Desalination and Water Treatment, 57:15, 6644-6651, DOI: 10.1080/19443994.2015.1012560, 2016.
- [12] Rusdianasari, A. Taqwa, Jaksen, and A. Syakdani, "Treatment of Landfill Leachate by Electrocoagulation using Aluminum Electrode", Matec Web of Conference, 101, 02010, 2017.
- [13] Jiadong Liu, Xin Ju, Bo Gao, and Lei Wang, "Effect of electrocoagulation on MBR under different power supply conditions", Biochemical Engineering Journal, vol. 152, 2019.
- [14] R. Gandhimathi, Albin Babu, P.V. Nidheesh, and S.T. Ramesh, "Laboratory study on leachate treatment by electrocoagulation using fly ash and bottom ash as supporting electrolytes", Journal of Hazardous, Toxic, and Radioactive Waste, vol. 19(3), 2015.
- [15] H. Djelal, Y. Lelievre & C. Ricordel, "Combination of electrocoagulation and biological treatment by bioaugmentation for landfill leachate", Desalination and Water Treatment, 54:11, 2986-2993, DOI: 10.1080/19443994.2014.908146, 2015.
- [16] Rusdianasari, A. Meidinariasty, I. Purnamasari, "Level decreasing kinetic model of heavy metal contents in the coal stockpile wastewater with electrocoagulation". Int. J. on Adv. Sci. Eng. and Information Tech. 5, 6, pp 387-391, 2015.

- [17] Erabee, I.K., Ahsan, A., Jose, B. et al. KSCE J Civ Eng 22: 1083. 2018, https://doi.org/10.1007/s12205-017-1430-z
- [18] Kamaruddin, M.A., Yusoff, M.S., Aziz, H.A. et al. Appl Water Sci 5: 113, 2015, https://doi.org/10.1007/s13201-014-0177-7
- [19] A. Fernandes, M.J. Pacheco, L. Ciriaco, and A. Lopes, "Review on the eletrochemical process for the treatment of sanitary landfill leachate: Present and Future", Applied Catalysis B: Environmental, Vol. 176-177, pp 183-200, 2015.
- [20] T.M. Shah, S. Ramaswani, J. Behrenddt, and R. Offerpahl, "Simultaneous removal of organics and ammonium-nitrogen from reverse osmosis concentrate of mature landfill leachate", Journal of Water Oricess Engineering, Vol. 9, pp 126-132, 2017.
- [21] N. Kasmuri and N. Aliah, "The treatment of landfill leachate by electrocoagulation to reduce heavy metals and ammonium-nitrogen", International Journal of Engineering Technology, Vol. 7(3.11), pp 109-112, 2018.
- [22] Rusdianasari, Y. Bow, A. Taqwa, "Treatment of coal stockpile wastewater by electrocoagulation using aluminum electrodes". Adv. Materials Res. 896, pp 145-148, 2014.
- [23] N.S.M Amdan, N.S.M. Zin, S.N.A.M. Salleh, and L.W.M. Zailani, "Addition of composite coagulant (polyaluminium chloride and tapioca flavor) into electrocoagulation (aluminum and ferum electrodes) for treatment of stabilized lecahate", Matec Web of conference 250, 06005, 2018.
- [24] M. Sadeghi, A. Fadaei, M. Tadrisi, A. Bay, and A. Naghizadeh, "Performance evaluation of a biological landfill leachate treatment plant and effluent treatment by electrocogaulation", Desalination and Water Treatment, Vol. 115, pp 82-87, 2018.
- [25] A. Roberto, F. Rudolfo, I. Christina, D. Estelita, A.N. Mudaros, C. Ribeiro, T.H. Bioba, and A.D. Kroumav, "New insights on abateemat of organic matter and reduction of toxicity from landfill leachate treated by the electrocoagulation process", Journal of Environmental Chemical Engineering, Vol. 5(6), pp 5448-5459, 2017.
- [26] O. Dia, P. Drogue, G. Buelna, R. Dube, and B.S. Ihren, "Electrocoagulation of bio-filtered landfill leachate: Fractionation of organic matter and influence of anode materials", Chemosphere, Vol. 168, pp 1136-1141, 2017.
- [27] Rusdianasari, Y. Bow, and T. Dewi. "Peat water treatment by electrocoagulation using aluminum electrodes", IOP Conf.Ser. 258 012013, 2019.