

## DAFTAR PUSTAKA

- [1] J. Guo, X. Zhang, F. Gu, H. Zhang, and Y. Fan, “Does air pollution stimulate electric vehicle sales? Empirical evidence from twenty major cities in China,” *J. Clean. Prod.*, vol. 249, 2020, doi: 10.1016/j.jclepro.2019.119372.
- [2] S. Goel, R. Sharma, and A. K. Rathore, “A review on barrier and challenges of electric vehicle in India and vehicle to grid optimisation,” *Transp. Eng.*, vol. 4, no. January, 2021, doi: 10.1016/j.treng.2021.100057.
- [3] S. Goel, R. Sharma, and A. K. Rathore, “A review on barrier and challenges of electric vehicle in India and vehicle to grid optimisation,” *Transp. Eng.*, vol. 4, no. January, p. 100057, 2021, doi: 10.1016/j.treng.2021.100057.
- [4] M. A. Hannan, M. M. Hoque, A. Hussain, Y. Yusof, and P. J. Ker, “State-of-the-Art and Energy Management System of Lithium-Ion Batteries in Electric Vehicle Applications: Issues and Recommendations,” *IEEE Access*, vol. 6, pp. 19362–19378, 2018, doi: 10.1109/ACCESS.2018.2817655.
- [5] J. Kim, J. Oh, and H. Lee, “Review on battery thermal management system for electric vehicles,” *Appl. Therm. Eng.*, vol. 149, no. November 2018, pp. 192–212, 2019, doi: 10.1016/j.applthermaleng.2018.12.020.
- [6] M. Schwarz, Q. Auzepy, and C. Knoeri, “Can electricity pricing leverage electric vehicles and battery storage to integrate high shares of solar photovoltaics ?,” *Appl. Energy*, vol. 277, no. March, p. 115548, 2020, doi: 10.1016/j.apenergy.2020.115548.
- [7] T. Daniela, D. B. Vincenzo, and M. Enrica, “Development of an on-line energy management strategy for hybrid electric vehicle,” *Energy Procedia*, vol. 148, no. Ati, pp. 106–113, 2018, doi: 10.1016/j.egypro.2018.08.037.
- [8] M. Ehsani, Y. Gao, and A. Emadi, “Hybrid Electric Vehicles,” *Mod. Electr. Hybrid Electr. Fuel Cell Veh.*, pp. 1–20, 2019, doi: 10.1201/9781420054002-5.
- [9] L. Engbroks, D. Görke, S. Schmiedler, T. Gödecke, B. Beyfuss, and B. Geringer, “Combined energy and thermal management for plug-in hybrid electric vehicles -analyses based on optimal control theory,” *IFAC-PapersOnLine*, vol. 52, no. 5, pp. 610–617, 2019, doi: 10.1016/j.ifacol.2019.09.097.
- [10] H. S. Kang, S. M. Kim, Y. Bak, and K. B. Lee, “A Controller Design for a Stability Improvement of an Integrated Charging System in Hybrid Electric Vehicle,” *IFAC-PapersOnLine*, vol. 52, no. 4, pp. 141–146, 2019, doi: 10.1016/j.ifacol.2019.08.169.
- [11] K. Ma, Z. Wang, H. Liu, H. Yu, and C. Wei, “Numerical investigation on

- fuzzy logic control energy management strategy of parallel hybrid electric vehicle,” *Energy Procedia*, vol. 158, pp. 2643–2648, 2019, doi: 10.1016/j.egypro.2019.02.016.
- [12] S. Carley, S. Siddiki, and S. Nicholson-Crotty, “Evolution of plug-in electric vehicle demand: Assessing consumer perceptions and intent to purchase over time,” *Transp. Res. Part D Transp. Environ.*, vol. 70, no. April, pp. 94–111, 2019, doi: 10.1016/j.trd.2019.04.002.
- [13] C. H. Chung, S. Jangra, Q. Lai, and X. Lin, “Optimization of Electric Vehicle Charging for Battery Maintenance and Degradation Management,” *IEEE Trans. Transp. Electrification*, vol. 6, no. 3, pp. 958–969, 2020, doi: 10.1109/TTE.2020.3000181.
- [14] Y. Wang, M. Kazemi, S. Nojavan, and K. Jermsittiparsert, “Robust design of off-grid solar-powered charging station for hydrogen and electric vehicles via robust optimization approach,” *Int. J. Hydrogen Energy*, vol. 45, no. 38, pp. 18995–19006, 2020, doi: 10.1016/j.ijhydene.2020.05.098.
- [15] H. Fu, Y. Han, J. Wang, and Q. Zhao, “A Novel Optimization of Plug-In Electric Vehicles Charging and Discharging Behaviors in Electrical Distribution Grid,” *J. Electr. Comput. Eng.*, vol. 2018, 2018, doi: 10.1155/2018/5091084.
- [16] S. Hussain, M. U. Ali, G. S. Park, S. H. Nengroo, M. A. Khan, and H. J. Kim, “A real-time bi-adaptive controller-based energy management system for battery–supercapacitor hybrid electric vehicles,” *Energies*, vol. 12, no. 24, 2019, doi: 10.3390/en12244662.
- [17] H. J. Bergveld Kruijt, Wanda S., Notten, P. H. L., *Battery management systems : design by modelling*. Dordrecht; Boston: Kluwer Academic, 2002.
- [18] A. Joseph and M. Shahidehpour, “BATTERY STORAGE SYSTEMS IN ELECTRIC POWER SYSTEMS Ami Joseph and Mohammad Shahidehpour,” pp. 1–8, 2006.
- [19] R. Dufo-López, T. Cortés-Arcos, J. S. Artal-Sevil, and J. L. Bernal-Agustín, “Comparison of lead-acid and li-ion batteries lifetime prediction models in stand-alone photovoltaic systems,” *Appl. Sci.*, vol. 11, no. 3, pp. 1–16, 2021, doi: 10.3390/app11031099.
- [20] A. Das and A. Ganesh, “A study paper on power management in electrical devices using Zigbee network,” *Souvenir 2015 IEEE Int. Adv. Comput. Conf. IACC 2015*, pp. 444–448, 2015, doi: 10.1109/IADCC.2015.7154747.
- [21] P. Ashkrof, G. Homem de Almeida Correia, and B. van Arem, “Analysis of the effect of charging needs on battery electric vehicle drivers’ route choice behaviour: A case study in the Netherlands,” *Transp. Res. Part D Transp. Environ.*, vol. 78, no. December 2019, p. 102206, 2020, doi: 10.1016/j.trd.2019.102206.

- [22] M. Yousefi, A. Hajizadeh, and M. N. Soltani, “A Comparison Study on Stochastic Modeling Methods for Home Energy Management Systems,” *IEEE Trans. Ind. Informatics*, vol. 15, no. 8, pp. 4799–4808, 2019, doi: 10.1109/tii.2019.2908431.
- [23] A. Geetha and C. Subramani, “A significant energy management control strategy for a hybrid source EV,” *Int. J. Electr. Comput. Eng.*, vol. 9, no. 6, pp. 4580–4585, 2019, doi: 10.11591/ijece.v9i6.pp4580-4585.
- [24] K. V. Singh, H. O. Bansal, and D. Singh, “Feed-forward modeling and real-time implementation of an intelligent fuzzy logic-based energy management strategy in a series–parallel hybrid electric vehicle to improve fuel economy,” *Electr. Eng.*, vol. 102, no. 2, pp. 967–987, 2020, doi: 10.1007/s00202-019-00914-6.
- [25] Y. Wang, F. Huang, B. Pan, Y. Li, and B. Liu, “Augmented system model-based online collaborative determination of lead–acid battery states for energy management of vehicles,” *Meas. Control (United Kingdom)*, vol. 54, no. 1–2, pp. 88–101, 2021, doi: 10.1177/0020294020983376.
- [26] M. Yue, S. Jemei, R. Gouriveau, and N. Zerhouni, “Review on Health-Conscious Energy Management Strategies for Fuel cell Hybrid Electric Vehicles : Degradation Models and Strategies,” 2019.
- [27] T. Teng, X. Zhang, H. Dong, and Q. Xue, “ScienceDirect A comprehensive review of energy management optimization strategies for fuel cell passenger vehicle,” *Int. J. Hydrogen Energy*, no. xxxx, 2020, doi: 10.1016/j.ijhydene.2019.12.202.
- [28] F. A. Tiano, G. Rizzo, and D. Marra, “Design and Optimization of a Charging Station for Electric Vehicles based on Compressed Air Energy Storage,” *IFAC-PapersOnLine*, vol. 51, no. 9, pp. 230–235, 2018, doi: 10.1016/j.ifacol.2018.07.038.
- [29] B. C. Chen, Y. Y. Wu, and H. C. Tsai, “Design and analysis of power management strategy for range extended electric vehicle using dynamic programming,” *Appl. Energy*, vol. 113, pp. 1764–1774, 2014, doi: 10.1016/j.apenergy.2013.08.018.
- [30] H. Hemi, J. Ghouili, and A. Cheriti, “Combination of Markov chain and optimal control solved by Pontryagin’s minimum principle for a fuel cell/supercapacitor vehicle,” *Energy Convers. Manag.*, vol. 91, pp. 387–393, 2015, doi: 10.1016/j.enconman.2014.12.035.
- [31] M. Jha, F. Blaabjerg, M. A. Khan, V. S. B. Kurukuru, and A. Haque, “Intelligent control of converter for electric vehicles charging station,” *Energies*, vol. 12, no. 12, 2019, doi: 10.3390/en12122334.
- [32] P. Ponce, B. MacCleery, L. A. Soriano, M. García, V. Leví, and A. Molina, “Expanding electric vehicles lifetime in power electronic stage using an optimized fuzzy logic controller,” *Int. J. Interact. Des. Manuf.*, 2021, doi:

10.1007/s12008-021-00794-w.

- [33] N. Sulaiman, M. A. Hannan, A. Mohamed, P. J. Ker, E. H. Majlan, and W. R. Wan Daud, "Optimization of energy management system for fuel-cell hybrid electric vehicles: Issues and recommendations," *Appl. Energy*, vol. 228, no. July, pp. 2061–2079, 2018, doi: 10.1016/j.apenergy.2018.07.087.
- [34] P. Wang, D. Wang, C. Zhu, Y. Yang, H. M. Abdullah, and M. A. Mohamed, "Stochastic management of hybrid AC/DC microgrids considering electric vehicles charging demands," *Energy Reports*, vol. 6, pp. 1338–1352, 2020, doi: 10.1016/j.egyr.2020.05.019.
- [35] P. Tejaswini and P. Sivraj, "Artificial intelligence based state of charge estimation of Li-ion battery for EV applications," *Proc. 5th Int. Conf. Commun. Electron. Syst. ICCES 2020*, no. Icces, pp. 1356–1361, 2020, doi: 10.1109/ICCES48766.2020.09137999.
- [36] M. Stighezza, V. Bianchi, and I. De Munari, "FPGA Implementation of an Ant Colony Optimization Based SVM Algorithm for State of Charge Estimation in Li-Ion Batteries," *Energies*, vol. 14, no. 21, 2021, doi: 10.3390/en14217064.
- [37] X. Li, Y. Wang, D. Yang, and Z. Chen, "Adaptive energy management strategy for fuel cell/battery hybrid vehicles using Pontryagin's Minimal Principle," *J. Power Sources*, vol. 440, no. August, p. 227105, 2019, doi: 10.1016/j.jpowsour.2019.227105.
- [38] D. Zhou, A. Al-Durra, I. Matraji, A. Ravey, and F. Gao, "Online Energy Management Strategy of Fuel Cell Hybrid Electric Vehicles: A Fractional-Order Extremum Seeking Method," *IEEE Trans. Ind. Electron.*, vol. 65, no. 8, pp. 6787–6799, 2018, doi: 10.1109/TIE.2018.2803723.
- [39] R. T. Meyer, R. A. Decarlo, and S. Pekarek, "Hybrid Model Predictive Power Management of a Battery-Supercapacitor Electric Vehicle," *Asian J. Control*, vol. 18, no. 1, pp. 150–165, 2016, doi: 10.1002/asjc.1259.
- [40] F. Jin, M. Wang, and C. Hu, "A fuzzy logic based power management strategy for hybrid energy storage system in hybrid electric vehicles considering battery degradation," *2016 IEEE Transp. Electrification Conf. Expo, ITEC 2016*, 2016, doi: 10.1109/ITEC.2016.7520207.
- [41] S. K. Jha, A. K. Yadav, and P. Gaur, "Power management for electric vehicle with PID and Fuzzy logic controllers," *Proc. Int. Conf. Electron. Commun. Aerosp. Technol. ICECA 2017*, vol. 2017-Janua, no. April 2017, pp. 56–61, 2017, doi: 10.1109/ICECA.2017.8212731.
- [42] C. H. Swetha, N. S. Jayalakshmi, K. M. Bhargavi, and P. B. Nempu, "Control Strategies for Power Management of PV/Battery System with Electric Vehicle," *2019 IEEE Int. Conf. Distrib. Comput. VLSI, Electr. Circuits Robot. Discov. 2019 - Proc.*, pp. 1–6, 2019, doi: 10.1109/DISCOVER47552.2019.9008082.

- [43] H. Saleeb, K. Sayed, A. Kassem, and R. Mostafa, "Power management strategy for battery electric vehicles," *IET Electr. Syst. Transp.*, vol. 9, no. 2, pp. 65–74, 2019, doi: 10.1049/iet-est.2018.5026.
- [44] N. P. Reddy, D. Padeloup, M. K. Zadeh, and R. Skjetne, "An Intelligent Power and Energy Management System for Fuel Cell/Battery Hybrid Electric Vehicle Using Reinforcement Learning," *ITEC 2019 - 2019 IEEE Transp. Electrif. Conf. Expo*, 2019, doi: 10.1109/ITEC.2019.8790451.
- [45] M. Giliberto, F. Arena, and G. Pau, "A fuzzy-based solution for optimized management of energy consumption in e-bikes," *J. Wirel. Mob. Networks, Ubiquitous Comput. Dependable Appl.*, vol. 10, no. 3, pp. 45–64, 2019, doi: 10.22667/JOWUA.2019.09.30.045.
- [46] S. Hussain, M. A. Ahmed, and Y. C. Kim, "Efficient Power Management Algorithm Based on Fuzzy Logic Inference for Electric Vehicles Parking Lot," *IEEE Access*, vol. 7, pp. 65467–65485, 2019, doi: 10.1109/ACCESS.2019.2917297.
- [47] Q. Zhang, L. Wang, G. Li, and Y. Liu, "A real-time energy management control strategy for battery and supercapacitor hybrid energy storage systems of pure electric vehicles," *J. Energy Storage*, vol. 31, no. July, p. 101721, 2020, doi: 10.1016/j.est.2020.101721.
- [48] S. Pietrosanti, F. Alasali, and W. Holderbaum, "Power management system for RTG crane using fuzzy logic controller," *Sustain. Energy Technol. Assessments*, vol. 37, no. January, p. 100639, 2020, doi: 10.1016/j.seta.2020.100639.
- [49] Y. Kim, M. Figueroa-Santos, N. Prakash, S. Baek, J. B. Siegel, and D. M. Rizzo, "Co-optimization of speed trajectory and power management for a fuel-cell/battery electric vehicle," *Appl. Energy*, vol. 260, no. May 2019, p. 114254, 2020, doi: 10.1016/j.apenergy.2019.114254.
- [50] R. Araria, A. Berkani, K. Negadi, F. Marignetti, and M. Boudiaf, "Performance analysis of DC-DC converter and DTC based fuzzy logic control for power management in electric vehicle application," *J. Eur. des Syst. Autom.*, vol. 53, no. 1, pp. 1–9, 2020, doi: 10.18280/jesa.530101.
- [51] A. K. Gautam, M. Tariq, J. P. Pandey, and K. S. Verma, "Optimal power management strategy of regenerative braking using fuzzy logic controller for BLDC Motor-Driven E-Rickshaw," *J. Intell. Fuzzy Syst.*, pp. 1–10, 2021, doi: 10.3233/jifs-189774.
- [52] C. Abdeselem, A. Othmane, G. Brahim, S. M. Amine, H. Oussama, and H. M. Amine, "Power management strategy based sugeno fuzzy logic rules in an electric wheelchair," *Int. J. Power Electron. Drive Syst.*, vol. 12, no. 2, pp. 1187–1195, 2021, doi: 10.11591/ijpeds.v12.i2.pp1187-1195.
- [53] S. M. Arif, T. T. Lie, B. C. Seet, S. Ayyadi, and K. Jensen, "Review of electric vehicle technologies, charging methods, standards and optimization

- techniques,” *Electron.*, vol. 10, no. 16, pp. 1–21, 2021, doi: 10.3390/electronics10161910.
- [54] S. Bozhkov, “Structure of the Model of Hybrid Electric Vehicle Energy Efficiency,” vol. 79, no. 3, pp. 76–79, 2021.
- [55] M. Ehsani, K. V. Singh, H. O. Bansal, and R. T. Mehrjardi, “State of the Art and Trends in Electric and Hybrid Electric Vehicles,” *Proc. IEEE*, vol. 109, no. 6, pp. 967–984, 2021, doi: 10.1109/JPROC.2021.3072788.
- [56] C. Mahmoudi, A. Flah, and L. Sbita, “2014 International Conference on Electrical Sciences and Technologies in Maghreb, CISTEM 2014,” *2014 Int. Conf. Electr. Sci. Technol. Maghreb, Cist. 2014*, p. 1088, 2014.
- [57] P. Nieuwenhuis, L. Cipcigan, and H. B. Sonder, *The electric vehicle revolution*. Elsevier Ltd, 2020.
- [58] “Dictionary of Energy,” vol. 737, no. 1991, p. 20110825, 2012, doi: 10.1016/B978-0-08-096811-7.50002-0.
- [59] M. C. Kocer *et al.*, “Assessment of battery storage technologies for a Turkish power network,” *Sustain.*, vol. 11, no. 13, 2019, doi: 10.3390/su11133669.
- [60] K. S. Boparai and R. Singh, *Electrochemical Energy Storage Using Batteries, Superconductors and Hybrid Technologies*. Elsevier Ltd., 2020.
- [61] Syafii, Y. Mayura, and A. El Gazaly, “Characteristics of lead-acid battery charging and discharging against residential load in tropical area,” *2019 16th Int. Conf. Qual. Res. QIR 2019 - Int. Symp. Electr. Comput. Eng.*, pp. 1–6, 2019, doi: 10.1109/QIR.2019.8898277.
- [62] R. Article, “A brief review on key technologies in the battery management system of electric vehicles,” 2018.
- [63] J. McDowall, “Batteries | Parallel and Series Connections,” *Encycl. Electrochem. Power Sources*, pp. 499–509, 2009, doi: 10.1016/B978-044452745-5.00850-9.
- [64] G. Pistoia, “Vehicle Applications,” *Batter. Oper. Devices Syst.*, pp. 321–378, 2009, doi: 10.1016/b978-0-444-53214-5.00005-4.
- [65] T. H. Wang and Y. W. P. Hong, “Learning-based energy management policy with battery depth-of-discharge considerations,” *2015 IEEE Glob. Conf. Signal Inf. Process. Glob. 2015*, pp. 992–996, 2016, doi: 10.1109/GlobalSIP.2015.7418346.
- [66] Wikipedia, “Sensor,” 2022, [Online]. Available: <https://en.wikipedia.org/wiki/Sensor#:~:text=From Wikipedia%2C the free encyclopedia>.
- [67] “PZEM-003 / 017 DC communication module,” Solar - Thailand.

- [68] D. Ibrahim, "Chapter 1 - Introduction," D. B. T.-A.-B. microcontroller projects using M. Ibrahim, Ed. Newnes, 2019, pp. 1–7.
- [69] M. Gaudenzi Asinelli, M. Serra Serra, J. Molera Marimòn, and J. Serra Espauella, "The smARTS\_Museum\_V1: An open hardware device for remote monitoring of Cultural Heritage indoor environments," *HardwareX*, vol. 4, 2018, doi: 10.1016/j.ohx.2018.e00028.
- [70] T. Qiang, G. Guangling, L. Hai, C. Lina, and W. Han, "Nodemcu-based Low-cost Smart Home Node Design," *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 435, no. 1, 2018, doi: 10.1088/1757-899X/435/1/012013.
- [71] A. Freund, "Relay," *EC M Electr. Constr. Maint.*, vol. 86, no. 1, pp. 79–85, 134, 1987, doi: 10.1002/9781119819035.ch5.
- [72] M. Xie, "Relay Channel," pp. 1–8, 2003, [Online]. Available: [https://en.wikipedia.org/wiki/Relay\\_channel#:~:text=relay channel is a probability model of the communication between a sender and a receiver aided by one or more intermediate relay nodes.](https://en.wikipedia.org/wiki/Relay_channel#:~:text=relay channel is a probability model of the communication between a sender and a receiver aided by one or more intermediate relay nodes.)
- [73] M. Bates, *Power Outputs*. Elsevier Ltd, 2014.
- [74] M. S. Wang, S. C. Chen, and C. H. Shih, "Speed control of brushless DC motor by adaptive network-based fuzzy inference," *Microsyst. Technol.*, vol. 24, no. 1, pp. 33–39, 2018, doi: 10.1007/s00542-016-3148-0.
- [75] Z. Wang, H. Jin, J. Guo, J. Su, and M. Wang, "Research on Control System of Three-phase Brushless DC Motor for Electric Vehicle," *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 274, no. 1, 2017, doi: 10.1088/1757-899X/274/1/012016.
- [76] R. Gambhir and A. K. Jha, "Brushless DC Motor : Construction and Applications," *Int. J. Eng. Sci.*, vol. 2, no. 5, pp. 72–77, 2013.
- [77] N. Chaker, I. Ben Salah, S. Tounsi, and R. Neji, "Design of Axial-Flux Motor for Traction Application," *J. Electromagn. Anal. Appl.*, vol. 01, no. 02, pp. 73–84, 2009, doi: 10.4236/jemaa.2009.12012.
- [78] G. Ellis, *Basics of the Electric Servomotor and Drive*. 2012.
- [79] A. R. Paul and M. George, "Brushless DC motor control using digital PWM techniques," *2011 - Int. Conf. Signal Process. Commun. Comput. Netw. Technol. ICSCCN-2011*, no. Icscn, pp. 733–738, 2011, doi: 10.1109/ICSCCN.2011.6024647.
- [80] I. Sinclair, "Active Components and Integrated Circuits," *Electron. Simpl.*, pp. 47–59, 2011, doi: 10.1016/b978-0-08-097063-9.10003-2.
- [81] G. Yan and N. F. O. Serteller, "Brushless direct current (BLDC) machine Bipolar - Unipolar Driving Circuit education study," *Procedia - Soc. Behav. Sci.*, vol. 2, no. 2, pp. 2694–2699, 2010, doi: 10.1016/j.sbspro.2010.03.398.

- [82] K. W. E. Cheng, B. P. Divakar, H. Wu, K. Ding, and H. F. Ho, “Battery-management system (BMS) and SOC development for electrical vehicles,” *IEEE Trans. Veh. Technol.*, vol. 60, no. 1, pp. 76–88, 2011, doi: 10.1109/TVT.2010.2089647.
- [83] G. Versluis and S. Thewissen, “User Interface,” *Xamarin.Forms Solut.*, pp. 35–107, 2019, doi: 10.1007/978-1-4842-4134-9\_2.
- [84] A. C. Bento, “An Experiment with Arduino Uno and Tft Nextion for Internet of Things,” *2018 Int. Conf. Recent Innov. Electr. Electron. Commun. Eng. ICRIEECE 2018*, no. July 2018, pp. 1238–1242, 2018, doi: 10.1109/ICRIEECE44171.2018.9008416.
- [85] M. Stangl, J. Pielmeier, C. Berger, S. Braunreuther, and G. Reinhart, “Development of a Web Based Monitoring System for a Distributed and Modern Production,” *Procedia CIRP*, vol. 52, pp. 222–227, 2016, doi: 10.1016/j.procir.2016.07.073.
- [86] V. Mahajan, P. Agarwal, and H. Om Gupta, “Chapter 3 - Power quality problems with renewable energy integration,” P. Sanjeevikumar, C. Sharmeela, J. B. Holm-Nielsen, and P. B. T.-P. Q. in M. P. S. Sivaraman, Eds. Academic Press, 2021, pp. 105–131.