

DAFTAR PUSTAKA

- [1] E. Permana, I. L. Tarigan, G. D. Rizki, and I. Lestari. (2019). "Analisis Mutu Karbon Aktif dari Cangkang Kelapa Sawit Menggunakan Larutan Aktifator $ZnCl_2$," *J. Teknol.*, vol. 12, no. 2, pp. 170–175.
- [2] F. Febriyanti, N. Fadila, A. S. Sanjaya, Y. Bindar, and A. Irawan, "Pemanfaatan Limbah Tandan Kosong Kelapa Sawit Menjadi Bio-Char, Bio-oil Dan Gas Dengan Metode Pirolisis," *J. Chemurg.*, vol. 3, no. 2, p. 12, 2019, doi: 10.30872/cm.g.v3i2.3578.
- [3] Ziza, N. (2015) „Aplikasi Pemanfaatan Asap Cair Redistilasi Berbahan Baku Sabut Kelapa untuk Memperpanjang Masa Simpan Ikan Tongkol (Euthynnus Affinis)", Universitas Lampung.
- [4] Erawati, E. *et al.* (2015) .Distilasi Asap Cair Hasil Pirolisis Limbah Serbuk Gergaji Kayu Glugu", *simposium Nasional RAPI XIV*, pp. 213-219.
- [5] Anggraini, S. P. A. dan Yuniningsih, S. (2017) „Optimalisasi Penggunaan Asap Cair dari Tempurung Kelapa sebagai Pengawet Alami pada Ikan Segar", *Jurnal Reka Buana*, 2(1), pp. 11-18.
- [6] Basyir, Azhar Rantawi. (2020). Karakteristik Bio Oil yang Menggunakan Bahan Baku Cangkang Kelapa Sawit dan Diproses dengan Metode Pirolisis. *Jurnal Citra Widya Edukasi. Politeknik Kelapa Sawit Citra Widya Edukasi.*
- [7] Wang, S., Cai, Q., Wang, X., Zhang, L., Wang, Y., & Luo, Z. (2014). Biogasoline production from the co-cracking of the distilled fraction of bio-oil and ethanol. *Energy & fuels*, 28(1), 115-122.
- [8] Ningrum, S. S. Y., & Anggraini, S. P. A. (2018). Pemurnian Asap Cair Terhadap Kinerja Reaktor Pirolisis Melalui Proses Filtrasi Zeolit Aktif. In *Prosiding SENTIKUIN (Seminar Nasional Teknologi Industri, Lingkungan dan Infrastruktur)* (Vol. 1, pp. B9-1).
- [9] Suandi, A., Supardi, N.I., Puspawan, A. (2016). Analisa Pengolahan Kelapa Sawit dengan Kapasitas Olah 30 ton/jam di PT. BIO Nusantara Teknologi. *Teknosia*, 2(17), 12-19.
- [10] Hudori, M. (2017). Perbandingan Kinerja Perkebunan Kelapa Sawit Indonesia dan Malaysia. *Jurnal Citra Widya Edukasi*, 9(1), 93-112.
- [11] Pusat Data dan Informasi. (2007). *Gambaran Sekilas Industri Minyak Kelapa Sawit*. Jakarta : Dirjen Perindustrian.
- [12] Badan Pusat Statistik. (2019). *Indonesian Oil Palm Statistics*, Katalog : Jakarta: Badan Pusat Statistik.
- [13] Yang, Haiping, et al. (2006). *Mechanism of Palm Oil Waste Pyrolysi in a Packed Bed*. *Energy & Fuels* Vol 20: 1321-1328
- [14] Yulianti, R dan Widya, A. (2017). *Proses Katalitik Pirolisis untuk Cracking Bitumen dari Asbuton dengan Katalis Zeolit Alam*. Skripsi. Surabaya:ITS.
- [15] Basu, P., (2010). *Biomassa Gasification and Pyrolysis Practical Design and Theory*. Elsevier.
- [16] M. A. F. Mazlan, Y. Uemura, N. B. Osman, and S. Yusup. (2015). "Characterizations of bio-char from fast pyrolysis of Meranti wood sawdust," *J. Phys. Conf. Ser.*, vol. 622, no. 1, doi: 10.1088/1742-6596/622/1/012054.
- [17] Venderbosch, R.H. and Prins, W. (2010). Review: Fast pyrolysis technology development. *Biofuel*, 4, pp. 178-208.

- [18] B. Mohanty and I. I. Abdullahi,. (2016). "Bioethanol production from lignocellulosic waste-A review," *Biosci. Biotechnol. Res. Asia*, vol. 13, no. 2, pp. 1153–1161, doi: 10.13005/bbra/2146.
- [19] Pamilia Coniwanti, Muhammad Dani, Zubeir Saleh Daulay. (2015). "Pembuatan Natrium Karboksimate Selulosa (Na-CMC) Dari Limbah Kulit Kacang Tanah". *Jurnal Teknik Kimia* No. 4, Vol. 21.
- [20] Mardina, P., Talalangi, A.I., Sitinjak, J.F.M., Nugroho, A., dan Fahrizal, M. R. (2013). Pengaruh Proses Delignifikasi Pada Produksi Glukosa Dari Tongkol Jagung Dengan Hidrolisis Asam Encer. *Konversi*. **2 (2)**: 17-23.
- [21] Mohanty, B., & Abdullahi, I. I. (2016). Bioethanol production from lignocellulosic waste-a review. *Biosciences Biotechnology Research Asia*, 13(2), 1153.
- [22] R. Sindhu, P. Binod, A. Pandey, S. Ankaram, Y. Duan, and M. K. Awasthi,. (2019). Biofuel production from biomass: Toward sustainable development. Elsevier B.V.
- [23] Fessenden, R.J dan J.S. Fessenden. (1982). *Kimia Organik*. Jilid 1&2. Edisi Ketiga. Jakarta: Erlangga..
- [24] Y. I. Lestari, N. Idiawati, and Harlia,. (2015). "Aktivitas Antibakteri Asap Cair Tandan Kosong Sawit Grade 2 yang Sebelumnya Diadsorpsi Zeolit Teraktivasi," *Jkk*, vol. 4, no. 4, pp. 45–52,.
- [25] F. Fauzan and M. Ikhwanus,. (2017). "Pemurnian Asap Cair Tempurung Kelapa Melalui Distilasi dan Filtrasi Menggunakan Zeolit dan Arang Aktif," *Pros. Semnastek*, no. p-ISSN : 2407 – 1846, pp. 1–2,.
- [26] S. P. A. Anggraini and S. Yuniningsih, (2017). "Optimalisasi penggunaan asap cair dari tempurung kelapa sebagai pengawet alami pada ikan segar," *J. Reka Buana*, vol. 2, no. 1, pp. 11–18,.
- [27] Gorbатов, V. M. *et al.* (1971). Liquid Smoke For Use in Cured Meat", *Food Tech* 25. pp. 71-77..
- [28] Karseno, Purnama Darmadji dan Rahayu, K.. (2000). Kajian sifat Fungsional Antibakteri Asap Cair dan Redestilat Total Asap Cair Kayu Karet (*Heveabrasiliensis*) terhadap Bakteri Patogen.", Seminar Nasional Industri Pangan.
- [29] Keputusan Direktorat Jendral Minyak dan Gas Bumi No: 933.K/10/DJM.S/2013. Tahun 2013 tentang Standar dan Mutu (Spesifikasi) Bahan Bakar Minyak Jenis Bensin 88 Yang di Pasarkan di Dalam Negeri. Jakarta: KESDM.
- [30] Keputusan Direktora Jendral Minyak dan Gas Bumi No: 0486.K/10/DJM.S/2017. Tahun 2017 tentang Standar dan Mutu (Spesifikasi) Bahan Bakar Minyak Jenis Bensin 90 Yang Dipasarkan Di Dalam Negeri. Jakarta: KESDM.
- [31] Keputusan Direktora Jendral Minyak dan Gas Bumi No: 0177.K/10/DJM.T/2018. Tahun 2018 tentang Standar dan Mutu (spesifikasi) Bahan Bakar Minyak Jenis Bensin (Gasoline) RON 98 yang Dipasarkan di Dalam Negeri. Jakarta: KESDM
- [32] D. Jones,. (1977). "An assessment of the value of examination of the hip in the newborn," *J. Bone Jt. Surg. - Ser. B*, vol. 59, no. 3, pp. 318–322, doi: 10.1302/0301-620x.59b3.893510.
- [33] ASTM. (1990). Standards and Literature References for Composite Material Second Edition. Philadelphia, PA : American Society for Testing and Materials
- [34] Qurratul'uyun, Ismi. Produksi Bahan Bakar Cair Hidrokarbon (C8-C13) Dari Limbah Plastik Polipropilena Hasil Konversi Katalitik dengan Variasi Jumlah

- Katalis AI-MCM-41. Institut Teknologi Sepuluh November Surabaya. Skripsi. 2017.
- [35] ASTM. (2012). Annual Book of ASTM Standar D-1298 Standar Test Method for Density, Relative Density (Specific Gravity), or API Gravity of Crude Petroleum and Liquid Petroleum Product by Hydrometer. Philadelphia: American Society for Testing and Material
- [36] W. W. Purwanto, D. Supramono, R. Muthia, and G. Annisa, (2012) “Konversi Limbah Kelapa Sawit Menjadi Bio-oil melalui Proses Catalytic Fast Pyrolysis dan Upgradingnya” Semin. Nas. Tek. Kim. Indones. dan Musyawarah Nas. APTEKINDO 2012, no. July 2016, pp. 1–10,.
- [37] Omar R, Idris A, Yunus R, Khalid K, Aida I. 2011. Characterization of empty fruit bunch for microwave-assisted pyrolysis. *Fuel*. 90: 1536-1544.
- [38] Lee, Y., J. Park, C. Ryu, K.S. Gang, W. Yang, Y. Park dan S. Hyun. (2013). Bioresource technology comparison of biochar properties from biomass residues produced by slow pyrolysis at 500°C. *Bioresource Technology* Vol. 148:196–201
- [39] Ahmad, R, Hamidin, N, Ali, UFM & Abidin, CZA. (2014), 'CHARACTERIZATION OF BIO- OIL FROM PALM KERNEL SHELL PYROLYSIS', *Journal of Mechanical Engineering and Sciences (JMES)*, University Putra Malaysia, vol. 7, no. December 2014, pp. 1134-40.
- [40] Silva LS, Gonzales DS, Villasenor P, Sanchez J, Valverde L. (2012). Thermogravimetric – Mass Spectrometric Analysis of Lignocellulosic and Marine Biomass Pyrolysis. *Bioresource Technology* 109:163-172.
- [41] Mardina, P., Talalangi, A.I., Sitingjak, J.F.M., Nugroho, A., dan Fahrizal, M. R. (2013). Pengaruh Proses Delignifikasi Pada Produksi Glukosa Dari Tongkol Jagung Dengan Hidrolisis Asam Encer. *Konversi*. 2 (2): 17-23.
- [42] Heriyanto, H., Sumbogo, S. M., Heriyanti, S. I., Sholehah, I., & Rahmawati, A. (2018). Synthesis of green diesel from waste cooking oil through hydrodeoxygenation technology with NiMo/ γ -Al₂O₃ catalysts. 1–6.
- [43] Lin, B. J., & Chen, W. H. (2015). Sugarcane bagasse pyrolysis in a carbon dioxide atmosphere with conventional and microwave-assisted heating. *Frontiers in Energy Research*, 3, 4.
- [44] Arend M., Nonnen T., Hoelderich W. F., Fischer J., & Groos J. (2011). Catalytic deoxygenation of oleic acid in continuous gas flow for oxygen reduction reaction in PEMFCs. *J Mater Chem* 22, 20977
- [45] Asikin-Mijan, N., Lee, H. V., Abdulkareem-Alsultan, G., Afandi, A., Taufiq-Yap, Y.H. (2017). production of green diesel via cleaner catalytic deoxygenation of *Jatropha curcas* oil. *Journal of Cleaner Production*, 167, 1048-1059. doi:10.1016/j.jclepro.2016.10.023.
- [46] Aziz I. (2019). Upgrading Crude Biodiesel of Using Cooking Oil Using H-Zeolite Catalyst. *Jurnal Kimia Valensi* Vol 5(1) 79-86.
- [47] Özener, O., Yüksek, L., Ergenç, A. T., & Özkan, M. (2014). Effects of soybean biodiesel on a DI diesel engine performance, emission and combustion characteristics. *Fuel*, 115, 875-883.
- [48] Zaher, F., Gad, M. S., Aly, S. M., Hamed, S. F., Abo-Elwafa, G. A., & Zahran, H. A. (2017). Catalytic cracking of vegetable oils for producing biofuel. *Egypt J Chem*, 60(2), 291-300.
- [49] Orozco, Laura M., David A.Echeverri, Lorena Sánchez, dan Luis A.Rios. 2017. Second- Generation Green Diesel from Castor Oil: Development of A New and

- Efficient Continuous- Production Process. *Chemical Engineering Journal*, vol. 322, pp. 149 – 156, Elsevier. DOI: <https://doi.org/10.1016/j.cej.2017.04.027>
- [50] PRé, (2014) “SIMAPRO Database Manual”. Pp.3—48.
- [51] Volta, Y. A., & Yusi, S. (2021). Life Cycle Assessment (LCA) in Pulp & Paper Mills: Comparison Between MFO With Biomass in Lime Kiln. In *4th Forum in Research, Science, and Technology (FIRST-T1-T2-2020)* (pp. 323-327). Atlantis Press.